

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET HARLECH OAK

PRODUCT DETAILS

CONSTRUCTION	<i>Engineered Wood</i>
SPECIES	<i>Oak</i>
WEAR LAYER	<i>4mm Oak</i>
BACKING	<i>Poplar</i>
THICKNESS	<i>15mm</i>
WIDTH	<i>190mm</i>
LENGTH	<i>1900mm</i>
PACK SIZE	<i>2.166m²</i>
PLANKS PER PACK	<i>6</i>
PACKS PER PALLET	<i>60</i>
GRADE	<i>Select</i>
FINISH	<i>Oiled</i>
JOINT TYPE	<i>Tongue & Groove</i>
BEVELLED EDGES	<i>All 4 Edges</i>
FIXING METHOD	<i>Floated, nailed or stuck down</i>
UNDERFLOOR HEATING	<i>Suitable if fully stuck down</i>
TOG RATING	<i>1.13</i>



TECHNICAL CRITERIA

ORIGIN	<i>Europe</i>
RESPONSIBLE CERTIFICATION	<i>FSC</i>
JANKA HARDNESS RATING	<i>1,360 lbf (6,000N)</i>
FORMALDEHYDE EMISSION	<i>E1</i>
PENTACHLOROPHENOL EMISSION	<i>ND</i>
REACTION TO FIRE	<i>Dfl s1</i>
THERMAL CONDUCTIVITY	<i>0.143 W / mK</i>

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	<i>20mm</i>
MAXIMUM SIZE OF DEAD KNOTS	<i>10mm</i>
HEARTWOOD	<i>Not Allowed</i>
SAPWOOD	<i>10%</i>
INSECT HOLES	<i>Not Allowed</i>
FILLER	<i>Allowed</i>
COLOUR VARIATION	<i>Limited</i>
SMALL CRACKS	<i>Not Allowed</i>
ROT	<i>Not Allowed</i>

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.