

SPECIFICATION SHEET

SOFT DISTINCTION SB

QUALITY
ORDER CODE

DATE: 12/08/2025
REPLACES: 2/09/2019

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

SOFT DISTINCTION SB SDI

± 400-500
COLLECTION
1/10" CUT PILE

SOLUTION DYED

ECCELENA 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.760
± 2.730

± 10,0
± 12,0
± 181.240
± 39,40
± 46,00

±
±

± 25
PILE IN

✓
✓

✓

✓

NO SHOCK
✓

933F035A

Cl. 23
Domestic Heavy



LC5 

Efl 

LOW RADIUS

HEAVY NON-DOMESTIC

QUALITY

DIMENSIONAL STABILITY

EN 986

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

(±)

250Hz

(±)

500Hz

(±)

1000Hz

(±)

2000Hz

(±)

4000Hz

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

THERMAL RETENTION

(±) m²K/W

ISO 8302

TOG rating

(±)

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

LIGHTFASTNESS

ISO 105-B02

RUBBINGFASTNESS DRY

ISO 105 X12

RUBBINGFASTNESS WET

ISO 105 X12

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

WATERFASTNESS STAINING

ISO 105-E01

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

COLOURS



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

SOFT DISTINCTION SB

≤

± 25



±

±

±

±

±

±

±

± 0,15



± 1,5

≤

≤

≤


≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

AVAILABLE
FROM

SB 400

SDI

SB 500

0042	ANEMONE	0042
0212	CAPPUCCINO	0212
0242	BISCUIT	0242
0244	SEASHORE	0244
0272	LIMESTONE	0272
0432	ELMWOOD	0432
0444	POLAR	0444
0462	HEMP	0462
0804	COAL	0804
0832	ASH	0832
0842	GREYSTONE	0842
0844	MOONSHINE	0844
0852	METAL	0852
0862	PALOMA	0862
0872	SILVER	0872
0874	TEAL GREY	0874
0882	MIST	0882
0884	OSHIROI	0884

(18)

(18)