

QUALITY
ORDER CODE

DATE: **22/05/2025**
REPLACES: 19/05/2025

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE
FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1
BS 4790

SWEET ELEGANCE SB
SWG

± 400-500
COLLECTION
1/10" CUT PILE

SOLUTION DYED

ECCELENA 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 2.190
± 3.160

± 16,0
± 18,0
± 151.690
± 39,40
± 38,50

±
±

± 25
PILE IN

✓
✓

✓

NO SHOCK
✓

Cl. 22
Domestic General/Medium



LC5



Efl

LOW RADIUS

HEAVY DOMESTIC / GENERAL NON-DOMESTIC

