



**Furlong Flooring®**  
First choice flooring for every room

## CHARISMA II PRODUCT SPECIFICATION

PRODUCT INFORMATION	PRODUCT SPECIFICATION
Type	Vinyl
Backing	Felt
Widths	2m/3m/4m
No. of Patterns	10
Thickness	2.80
Wear Layer	0.40mm
Wear Layer Treatment	PU Coating
Total Weight	1950g/m <sup>2</sup>
Guarantee	15 Years
Slip Resistant	R10
European Class EN ISO 10874	Class 23-32
Standard Roll length	30m
Standard Roll Weight	121kg (2m), 182kg (3m), 242kg (4m)
Acoustic Insulation	17dB
Suitable for underfloor heating EN 12524	Yes
Inflammability	cfl-S1
TOG Rating/Thermal Resistance	0,0112 m <sup>2</sup> K/W / 0.11 TOG
Thermal Conductivity	0,25 W / mK
Loose Lay	24m <sup>2</sup>
Resistance to household chemicals	Very good





**Furlong Flooring®**

First choice flooring for every room

## CHARISMA II PRODUCT SPECIFICATION

COLOURS	FORMAT	COLOUR ID	Pattern repeat	Plank/Tile size
Augusta	Tiles	GC701	99.5x100	20x20
Bradley	Tiles	GC702	99.5x100	20x20
Defiant	Tiles	GC703	99.5x100	33.3x33.3
Hesperus	Tiles	GC704	99.5x100	33.3x33.3
Kimball	Random	GC705	100x100	0x0
Minos	Random	GC706	100x100	0x0
Ripinski	Tiles	GC707	99.5x120	25x40
Shand	Tiles	GC708	99.5x120	25x40
Tallac	Tiles	GC709	100x100	25x25
Wordie	Tiles	GC710	199x100	0x0



Easy to Care



Suitable  
for bathrooms



Slip Resistant



Sound  
Absorbing



**DARTFORD**  
01322 628700  
**PRESTON**  
01772 316155

**STONEHOUSE**  
01452 228480  
**DUBLIN**  
+353-1-4092000



Alternatively, visit [furlongflooring.com](http://furlongflooring.com)  
or email [enquiries@furlongflooring.com](mailto:enquiries@furlongflooring.com)

Follow us on

