


GeorgiaTex - Technical information

Domestic wear warranty		12 years
Classification	ISO 10874	Class 23 (heavy domestic) Class 31 (moderate commercial)
Thickness	EN ISO 24346	2.5mm
Wear layer	EN ISO 24340	0.25mm
Abrasion group	EN 660-2	T
Total weight	EN ISO 23997	1550 g/m ²
Roll widths	EN ISO 24341	2, 3, 4 & 5m
Standard roll length	EN ISO 24341	30m (approx.)
Slip resistance	EN 13893	≥ 0.60 (DS)
Slip resistance (ramp test with oil)	DIN 51130	R10
Reaction to fire	EN 13501-1	Bfl-s1
Impact sound improvement	EN ISO 717/2	Lw 16 dB
Static electrical propensity	EN 1815	< 2kV on concrete
Dimensional stability	EN ISO 23999	≤ 0.40%
Curling	EN ISO 23999	≤ 8mm
Residual indentation	EN ISO 24343-1	≤ 0.35mm
Underfloor heating	EN 12667	Suitable (max 27°C)
Thermal resistance	ISO 8302	0.025 m.K/W
Thermal conductivity	EN 12524	0.10 W/(m.K)
Light stability	ISO 105-B02	≥ 6°
Chemical resistance	ISO 26987	Resistant
Pendulum test	CENTS 15676:2007	+38
Cold welding	Werner Müller	Type A



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)

Our products are classified as A+ for the emission of volatile substances in inside air



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



Ortho-phthalates free

100% Ortho-phthalate free