

Pebble Beach Super technical information

Properties	Standard	Unit	Value
Wear warranty			7 year domestic
Usage classification	EN 1307	Class	22 (general domestic)
Tuft gauge	ISO 2424	COC	1/8 cut pile
Fibre	ISO 2424		100% polypropylene
Backing	ISO 2424		Action bac and felt back
Roll widths	EN 986	m	4 & 5 (± 1%)
Tog rating			0.9
Pile weight	ISO 8543	g/m ²	750
Total weight	ISO 8543	g/m ²	1585/1635 (± 15%)
Pile height	ISO 1765	mm	7
Number of knots	ISO 1763	m ²	141,840 (-7.5%, +10%)
Fire classification	EN 13501-1	Class	Efl
Light fastness	105-B02		≥ 5
Wearebility	105-X12		≥ 4
Water fastness	105-E01		≥ 4
Underfloor heating suitable			Yes, refer to tog rating



Pebble Beach Elite technical information

Properties	Standard	Unit	Value
Wear warranty			12 year domestic
Usage classification	EN 1307	Class	23 (heavy domestic)
Tuft gauge	ISO 2424	COC	1/8 cut pile
Fibre	ISO 2424		100% polypropylene
Backing	ISO 2424		Action bac
Roll widths	EN 986	m	4 & 5 (± 1%)
Tog rating			1.2
Pile weight	ISO 8543	g/m ²	1200
Total weight	ISO 8543	g/m ²	1835 (± 15%)
Pile height	ISO 1765	mm	8
Number of knots	ISO 1763	m ²	157,600 (-7.5%, +10%)
Fire classification	EN 13501-1	Class	Efl
Light fastness	105-B02		≥ 5
Wearebility	105-X12		≥ 4
Water fastness	105-E01		≥ 4
Underfloor heating suitable			Yes, refer to tog rating



Pebble Beach Luxury technical information

Properties	Standard	Unit	Value
Wear warranty			15 year domestic
Usage classification	EN 1307	Class	23 (heavy domestic)
Tuft gauge	ISO 2424	COC	1/8 cut pile
Fibre	ISO 2424		100% polypropylene
Backing	ISO 2424		Action bac
Roll widths	EN 986	m	4 & 5 (± 1%)
Tog rating			1.6
Pile weight	ISO 8543	g/m ²	1800
Total weight	ISO 8543	g/m ²	2360 (± 15%)
Pile height	ISO 1765	mm	11
Number of knots	ISO 1763	m ²	197,000 (-7.5%, +10%)
Fire classification	EN 13501-1	Class	Efl
Light fastness	105-B02		≥ 5
Wearebility	105-X12		≥ 4
Water fastness	105-E01		≥ 4
Underfloor heating suitable			Yes, refer to tog rating



UK
CA

CE

