


technical specifications

Product Description	Multilevel Loop
Yarn	100% Solution Dyed Nylon 6 (Polyamide-PA)
Tile Dimensions	50cm x 50cm
Pile Yarn Weight	770g/m ²
Total Weight	4200g/m ²
Pile Height	5mm
Total Thickness	7.5mm
Construction	1/12th gauge 55 stitches
Tufts per m ² / Pile Density	259,842/m ²
Backing Description	BioBase[®] recycled backing (recycled BS EN ISO 14021)
Wear Classification	Class 33 heavy commercial use (BS EN 1307)
Luxury Rating Class	LC3
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating: 0.47
Castor Chair Rating	Pass - continuous use (BS EN 985)
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 10140-3:2010 25dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 42.7dB
Number Of Tiles Per Box	20 (5m ²)
VOC	Class A+
Warranty	15 years



eco₂matters[®]

We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **eco₂matters[®]** sustainability goals, supported by the independently 3rd party verified **eco₂matters[®]** ecosystem.



tiltnturn[®] is a 770g product which reflects the amazing effects of light and shadow which surround us every day. The design and the colour palette are inspired by how light catches different planes within architectural structures, creating changing shadows and varying lines.



tiltnturn[®] is **low carbon**



Burmatex[®] reco₂very take back service provides a no landfill solution for your used tiles



tiltnturn[®] uses 100% Solution Dyed Nylon 6 yarn



Burmatex[®] products are made using 100% certified **renewable** electricity



tiltnturn[®] uses **BioBase[®] recycled** backing



eco₂matters[®] declarations are independently 3rd party verified

EPD
Burmatex[®] products are supported by 3rd party independently verified, product specific EPD's

LEED
Burmatex[®] products contribute towards Leed accreditation

SKA
Burmatex[®] products adhere to SKA standards

WELL Building Standards
Burmatex[®] products contribute to WELL Building Standards

Contact Us
T +44 (0) 1924 262 525
email: sales@burmatex.co.uk

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 0AN, United Kingdom

This shade card is the property of Burmatex[®]
Made from **eco laminate** and **100% recyclable card**

LRV values

Product code	Product colour name	CIE Y
34201	silver pitch	23.73
34202	zinc facet	10.42
34203	grey horizon	7.21
34204	gold patina	7.81
34205	light angle	15.47
34206	sky tint	14.38
34207	blue facade	4.53
34208	coal layer	4.10
34209	clay screen	14.99
34210	metal edge	11.30
34211	green space	8.31
34212	ash profile	5.62