Homestyle

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	EN ISO 10874	22 General/Medium
Binder content	ISO 11638	Type I
Characteristics	**Norm**	**Tarkett Value**
Total thickness	ISO 24346	2.50 mm
Wear layer thickness	ISO 24340	0.15 mm
Total weight	ISO 23997	1430 g/m²
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance	EN 14041	0007-0083-DOP-2024-10
Reaction to fire	EN 13501-1	Cfl-s1
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0.30)
Slip resistance (DIN 51130)	DIN 51130	R10
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance (m² K/W)	ISO 10456	0.04 m²•K/W
Technical Performance	**Norm**	**Tarkett Value**
Residual indentation	EN ISO 24343-1	≤ 0.35 mm
Impact sound reduction - ΔLw	EN ISO 717-2	19 dB
Colour fastness to light	ISO 105-B02	≥ 6
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Dimensional stability	EN ISO 23999	≤ 0,15 % Average measured value : ≤ 0.15 %
Sustainability, Environment & Indoor Air Quality	**Norm**	**Tarkett Value**
Total recycled content		21 %
Phthalate free		Yes
TVOC emissions after 28 days	EN 16516	Gold
BREEAM rating		A+
Formaldehyde emission		E1
Material Health Statement		Yes
French emissions label		A+
Allergy UK Seal Of Approval		Approved
Dimensions and designs		
Roll		Roll 2x30m Roll 3 x 30 m Roll 4 x 30 m
Number of designs available		12



The above information is subject to modification for the benefit of further improvement (14/01/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett