

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET

York Solid Oak Flooring

PRODUCT DETAILS

CONSTRUCTION	<i>Solid Wood</i>
SPECIES	<i>Oak</i>
THICKNESS	<i>18mm</i>
WIDTH	<i>150mm</i>
LENGTH	<i>300-1600mm</i>
PACK SIZE	<i>1.98m²</i>
PLANKS PER PACK	<i>Variable</i>
PACKS PER PALLET	<i>52</i>
GRADE	<i>Rustic</i>
FINISH	<i>Brushed & Matt Lacquered</i>
JOINT TYPE	<i>Tongue & Groove</i>
BEVELLED EDGES	<i>All 4 Edges</i>
FIXING METHOD	<i>Stick down or secret nail</i>
UNDERFLOOR HEATING	<i>Not advised</i>



GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	<i>50mm</i>
MAXIMUM SIZE OF DEAD KNOTS	<i>30mm</i>
HEARTWOOD	<i>Allowed</i>
SAPWOOD	<i>Allowed</i>
INSECT HOLES	<i>Not Allowed</i>
FILLER	<i>Allowed</i>
COLOUR VARIATION	<i>Allowed</i>
SMALL CRACKS	<i>Allowed</i>
ROT	<i>Not Allowed</i>

TECHNICAL CRITERIA

ORIGIN	<i>Europe</i>
RESPONSIBLE CERTIFICATION	<i>FSC</i>
JANKA HARDNESS RATING	<i>1,360 lbf (6,000N)</i>
FORMALDEHYDE EMISSION	<i>E1</i>
PENTACHLOROPHENOL EMISSION	<i>ND</i>
REACTION TO FIRE	<i>Dfl s1</i>
THERMAL CONDUCTIVITY	<i>0.143 W / mK</i>

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.