NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET

Chepstow Oak - Unfinished, Lacquered or Oiled

PRODUCT DETAILS

CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	6mm Oak
BACKING	Eucalyptus Ply
THICKNESS	21mm
WIDTH	189mm
LENGTH	1860mm
PACK SIZE	2.11m ²
PLANKS PER PACK	6
PACKS PER PALLET	40
GRADE	Rustic
FINISH	Choice of Three
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if fully stuck down
TOG RATING	

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC
JANKA HARDNESS RATING	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION	EI
PENTACHLOROPHENOL EMISSION	ND
REACTION TO FIRE	Dfl sl
THERMAL CONDUCTIVITY	0.16 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.





NATURALLY INSPIRED FLOORING

TECHNIC AL DATA SHEET CHEPSTOW RUSTIC OAK OILED

PRODUCT DETAILS

PRODUCT CODE	65-HBO-001
	Engineered Wood
	<u> </u>
SPECIES	Oak
WEAR LAYER	6mm Oak
BACKING	Eucalyptus Ply
THICKNESS	21mm
WIDTH	189mm
LENGTH	1860mm
PACK SIZE	2.11m ²
PLANKS PER PACK	6
PACKS PER PALLET	40
GRADE	Rustic
FINISH	Brushed & Oiled
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if fully stuck down
TOG RATING	1.2

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



TECHNICAL CRITERIA

Europe
FSC
bf (6,000N)
EI
ND
Dfl s1
).16 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.





NATURALLY INSPIRED FLOORING

TECHNIC AL DATA SHEET CHEPSTOW RUSTIC OAK LACQUERED

PRODUCT DETAILS PRODUCT CODE

PRODUCT CODE	65-HML-001
CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	6mm Oak
BACKING	Eucalyptus Ply
THICKNESS	21mm
WIDTH	189mm
LENGTH	1860mm
PACK SIZE	2.11m ²
PLANKS PER PACK	6
PACKS PER PALLET	40
GRADE	Rustic
FINISH	Matt Lacquered
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if fully stuck down
TOG RATING	1.2

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



TECHNICAL CRITERIA

Europe
FSC
(6,000N)
EI
ND
Dfl s1
óW/mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.





NATURALLY INSPIRED FLOORING

TECHNIC AL DATA SHEET CHEPSTOW RUSTIC OAK 240

PRODUCT DETAILS

PRODUCT CODE	65-HBO-002
CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	6mm Oak
BACKING	Eucalyptus Ply
THICKNESS	21mm
WIDTH	240mm
LENGTH	2200mm
PACK SIZE	2.11m²
PLANKS PER PACK	4
PACKS PER PALLET	35
GRADE	Rustic
FINISH	Brushed & Oiled
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if fully stuck down
TOG RATING	1.2
7001011110	1.2

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC
JANKA HARDNESS RATING	lbf (6,000N)
FORMALDEHYDE EMISSION	EI
PENTACHLOROPHENOL EMISSION	ND
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	0.16 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.



