



**COMMITTED
TO THE HEALTH
OF ONE**
WWW.FORBO-FLOORING.COM/CHO

Technical specifications

Marmoleum Click meets the requirements of EN 14085

Marmoleum Click		
	Total thickness	EN-ISO 24346 9.8 mm
	Nominal thickness Marmoleum	EN-ISO 24346 2.5 mm
	Locking system	5G
	Domestic: heavy	EN-ISO 10874 Class 23
	Commercial: heavy	EN-ISO 10874 Class 33
	Tile/panel size	EN ISO 24341 30 x 30 cm 60 x 30 cm 90 x 30 cm
	Residual indentation	EN-ISO 24343-1 ≤ 0.15 mm
	Castor chair resistance	EN 425 Suitable for office chairs with castors.
	Light fastness	EN-ISO 105-B02 Method 3: blue scale minimum 6.
	Resistance to chemicals	EN-ISO 26987 Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis.
	Bacteriostatic properties	Marmoleum has natural bacteriostatic properties, which are confirmed by independent laboratories, even against the bacteria MRSA.
	Cigarette resistance	EN 1399 Marks left on linoleum as a result of stubbed-out cigarettes can be removed.
	Slip resistance	DIN 51130 R9
	Acoustical impact sound reduction	EN ISO 717-2 > 17 dB ≥ 21 dB (installed on Forbo foam)
	Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact.

EN 14041



0101601_DoP-511

Marmoleum Click meets the requirements of EN 14041

	Reaction to fire	EN 13501-1 C _s - s1
	Formaldehyde emission	EN ISO 717-1 E1
	Slip resistance	EN 13893 DS: ≥ 0.30
	Body voltage	EN 1815 < 2 kV
	Thermal conductivity	EN 12524 0.15 W/m-K

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

