



**Furlong Flooring®**  
First choice flooring for every room

## RIVER PRODUCT SPECIFICATION

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Collection	River	
Thickness	8mm	EN 13329+A2
Width	197mm	EN 13329+A2
Length	1205mm	EN 13329+A2
Surface	Authentic	
Quantity/weight per box (PU)	8 pieces = 1.9m <sup>2</sup> /approx 14 kg	
Quantity/weight per pallet	56 PU= 106.4 m <sup>2</sup> /approx 810 kg	
Class	32	EN13329 + A2
Abrasion Resistance	AC4	EN13329 + A2
Thickness Swelling	≤18	ISO 24336
Surface Swelling (Assembled Joint)	Qualitative Rating ≤2 (1-5) Quantative Rating ≤0,3mm	ISO 4760 (Nalfa 72h)
Resistance to Impact	Small Ball ≥12 N Large Ball ≥750mm	EN 13329+A2
Warranty Domestic/commercial	15/10 Years	
Resistance to Staining	Min.5 (group 1 and 2) Min4. (group 3)	EN 438-2_5
Surface Soundness	≥1.25 N/mm <sup>2</sup>	EN 13329+A2
Lock Strength	Length fl0,2 ≥ 1 kN/m Width fs0,2 ≥2 kN/m	ISO 24334
Effect of Castor Chair	25.000 Cycles - No Damage	EN 425:2002
Effect of a Furniture Leg	No Damage	EN 424
Opening Between Elements	≤0,20mm	EN 13329+A2
Height Difference Between Elements	≤0,15mm	EN 13329+A2
Moisture Content	4-10%	EN 322
Fire Resistance	CflS1	EN 9239-1
Formaldehyde Release	E0≤1,75 1,75≤E1≤3,5 mg/m <sup>2</sup> h	EN 12460-3
Slip Resistance	DS	EN 14041:2008
Thermal Conductivity	0.148 W/(m*K)	EN 12667:2001
Sound Rating	14dB	ISO 717-2





## RIVER PRODUCT SPECIFICATION

COLOURS	ITEM
Danube Oak	FRV001
Tigris Oak	FRV002
Delaware Oak	FRV003
Ganges Oak	FRV004
Thames Oak	FRV005
Nile Oak	FRV006
Trent Oak	FRV007
Erne Oak	FRV008

**Bevel**

Bevelled on 4 edges.



Water Resistant - up to  
72 Hours



Eco friendly flooring.



AC4 - Impact  
Resistant



Uni-Click  
Fitting



**DARTFORD**  
01322 628700  
**PRESTON**  
01772 316155

**STONEHOUSE**  
01452 228480  
**DUBLIN**  
+353-1-4092000



Alternatively, visit [furlongflooring.com](http://furlongflooring.com)  
or email [enquiries@furlongflooring.com](mailto:enquiries@furlongflooring.com)

Follow us on

