


Boho Bliss technical specification

Domestic wear warranty		10 years
Classification	ISO 10874	Heavy domestic (class 23) Moderate commercial (class 31)
Thickness	EN ISO 24346	2.5mm
Wear layer	EN ISO 24340	0.25mm
Abrasion group	EN 660-2	T
Total Weight	EN ISO 23997	1360g/m ²
Roll Widths	EN ISO 24341	2, 3 & 4m
Standard roll length	EN ISO 24341	+/- 25m
Slip resistance	EN 13893	> 0.60
Slip resistance (ramp test with oil)	DIN 51130	R10
Reaction to fire	EN 13501-1	Bfl-s1
Impact sound improvement	EN ISO 717/2	16 dB
Static electrical propensity	EN 1815	< 2kV on concrete
Dimensional stability	EN ISO 23999	≤ 0.40%
Curling	EN ISO 23999	≤ 8mm
Residual indentation	EN ISO 24343-1	≤ 0.35mm
Underfloor heating	EN 12667	Suitable (max 27°C)
Thermal resistance	ISO 8302	0.027 m ² .K/W
Thermal conductivity	EN 12524	0.09 W/(m.K)
Light stability	ISO 105-B02	≥ 6-7°
Chemical resistance	ISO 26987	Resistant
Cold welding	Werner Müller	Type A



Our products are classified as A+ for the emission of volatile substances in inside air



100% Ortho-phthalate free