

QUALITY
ORDER CODE

DATE: 17/03/2023
REPLACES: 16/12/2021

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

SOFT PERFECTION SB
SPE

± 400-500
COLLECTION
1/10" CUT PILE

SOLUTION DYED

ECCELENA 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 2.640
± 3.590

± 15,0
± 17,0
± 185.180
± 39,40
± 47,00

±
±

± 25
PILE IN

✓
✓

NO SHOCK
✓

FF24EDC2

Cl. 22
Domestic General/Medium



LC5






Efl



Heavy non-domestic

QUALITY

DIMENSIONAL STABILITY			EN 986	≤
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 25 
SOUND ABSORPTION	(±)	α_s	ISO 354 - 125 Hz	±
	(±)		250Hz	±
	(±)		500Hz	±
	(±)		1000Hz	±
	(±)		2000Hz	±
	(±)		4000Hz	±
SOUND ABSORPTION	(±)	α_w	EN ISO 11654	±
THERMAL RETENTION	(±) m²K/W		ISO 8302	± 0,175 
TOG rating	(±)			± 1,75
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤
SURFACE RESISTANCE R _{oT}	(±) ohm		ISO 10965	≤
SURFACE RESISTANCE R _{dT}	(±) ohm		ISO 10965	≤
LIGHTFASTNESS			ISO 105-B02	≥ 5 
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 3-4
WATERFASTNESS STAINING			ISO 105-E01	≥ 2-3

SOFT PERFECTION SB

≤

± 25



±

±

±

±

±

±

±

± 0,175



± 1,75

≤

≤

≤

≥ 5




≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB 400	SPE	SB 500
0242	BISCUIT	0242
0272	LIMESTONE	0272
0432	ELMWOOD	0432
0462	HEMP	0462
0832	ASH	0832
0842	GREYSTONE	0842
0844	MOONSHINE	0844
0862	PALOMA	0862
0872	SILVER	0872
0882	MIST	0882

SB 400	SPE	SB 500



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE