

QUALITY
ORDER CODE

DATE: 9/10/2024
REPLACES: 25/06/2019

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

PATINA SMB
UTO

± 400 & 500
COLLECTION
1/10" TWIST

PIECE DYED

100% TRIEXTA
SMARTSTRAND

WOVEN

SMART BACK

± 1.235
± 2.200

± 8,0
± 10,0
± 153.660
± 39,40
± 39,00

±
±

± 25
PILE OUT

✓
✓
✓

✓

ANTISTATIC
✓

1072CEAB

CL.23 / CL.31
Domestic heavy / Commercial Moderate






LC4



Cfl-s1




QUALITY

DIMENSIONAL STABILITY			EN 986	≤	
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 25 	
SOUND ABSORPTION	(±)	α_s	ISO 354 - 125 Hz	±	
	(±)			250Hz	±
	(±)			500Hz	±
	(±)			1000Hz	±
	(±)			2000Hz	±
	(±)			4000Hz	±
SOUND ABSORPTION	(±)	α_w	EN ISO 11654	±	
THERMAL RETENTION	(±) m²K/W		ISO 8302	± 0,125 	
TOG rating	(±)			± 1,25	
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤ 2000 	
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤	
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤	
LIGHTFASTNESS			ISO 105-B02	≥ 5	
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4	
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3	
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 3-4	
WATERFASTNESS STAINING			ISO 105-E01	≥ 2-3	

PATINA SMB

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SMB 400	UTO	SMB 500
0240	CREAM	0240
0330	APRICOT	0330
0370	GOLD	0370
0403	DARK CLOVE	0403
0413	PIER	0413
0420	CORNSTALK	0420
0430	BAMBOO MAT	0430
0440	IVORY	0440
0453	SEASALT	0453
0590	MOSS	0590
0713	BLUE PEACOCK	0713
0810	CHARCOAL	0810
0823	RAINSOWER	0823
0830	ASH	0830
0833	TITANIUM	0833
0850	MOONBEAM	0850
0860	GRANITE	0860
0863	HAZY GREY	0863

SMB 400	UTO	SMB 500



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE