

QUALITY
ORDER CODE

DATE: **3/02/2023**
REPLACES: 21/04/2022

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING ✓
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

BOULEVARD SMB
BOU

± 400 & 500
COLLECTION
1/10" TWIST

PIECE DYED

PES
Halcyon

WOVEN

SMART BACK

± 1.400
± 2.370

± 9,0
± 11,0
± 157.600
± 39,40
± 40,00

±
±

± 25
PILE IN

✓
✓

✓

4DCAA9D3

Cl. 23
Domestic Heavy



LC5



Cfl-s1



QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²K/W

ISO 8302

± 0,13



TOG rating

(±)

± 1,3

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE R_{oT}

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE R_{dT}

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5



RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE
FROM

AVAILABLE
FROM

<u>SMB 400</u>	<u>BOU</u>	<u>SMB 500</u>
0180	RUM	0180
0240	CREAM	0240
0260	CAMEL	0260
0310	RUST	0310
0410	LEATHER	0410
0430	BAMBOO MAT	0430
0450	SAND	0450
0470	ANGORA	0470
0720	BLUE CAPE	0720
0820	SLATE	0820
0830	ASH	0830
0860	GRANITE	0860
0870	SILVER	0870
0880	PEARL	0880

<u>SMB 400</u>	<u>BOU</u>	<u>SMB 500</u>
----------------	------------	----------------



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE