



Furlong Flooring®
First choice flooring for every room

SIRONA PRODUCT SPECIFICATION

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	18	18
m ² per pack	4.66m ²	3.90m ²
Weight per pack	15.64kg	13.26kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2 mm	ISO 24346:2006-10
Wear Layer	0.3mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance /Tog Rating	0.01 m ² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23- Heavy Domestic Class 31-Light Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501
Scratch Resistance	MSR-A2, MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25 mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/R10	EN 13893
Residual Indentation	Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	ΔLw = 4 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	15 Year Residential 5 Year Commercial	





Furlong Flooring®
First choice flooring for every room

SIRONA PRODUCT SPECIFICATION

COLOURS	PLANKS	TILES
Hamilton Oak	22121	
Pulaski Oak	22232	
Glade Oak	22315	
Cheriton Oak	22325	
Alberta Oak	22329	
Louisa Oak	22856	
Monterey Oak	22934	
Keysville Oak	24235	
Bloxom Oak	24241	
Duffield Oak	24279	
Fincastle Oak	24863	
Saltville Oak	24961	
Kitts Stone		46522
Cruz Stone		46541
Nevis Stone		46561
Tillar Stone		46960



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com
or email enquiries@furlongflooring.com

Follow us on

