

QUALITY
ORDER CODE

DATE: **8/05/2023**
REPLACES: 25/01/2023

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

**SOFIA KT
SOK**

± 400 & 500
COLLECTION
5/64" SAXONY

PIECE DYED

100% TRIEXTA
SMARTSTRAND



WOVEN

TEXTILE BACKING C-BACK

± 2.220
± 3.287

± 10,5
± 13,0
± 277.240
± 50,40
± 55,00

±
±

± 25
PILE IN

✓
✓

✓

ANTISTATIC
✓

E23DF478

Cl. 23
Domestic Heavy









LC5



Cfl-s1



				SOFIA KT	
QUALITY					
DIMENSIONAL STABILITY			EN 986	≤	
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 25	
SOUND ABSORPTION	(±)	α_s	ISO 354 - 125 Hz	±	
	(±)		250Hz	±	
	(±)		500Hz	±	
	(±)		1000Hz	±	
	(±)		2000Hz	±	
	(±)		4000Hz	±	
SOUND ABSORPTION	(±)	α_w	EN ISO 11654	±	
THERMAL RETENTION	(±) m²K/W		ISO 8302	± 0,17	
TOG rating	(±)			± 1,7	
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤ 2000	
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤	
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤	
LIGHTFASTNESS			ISO 105-B02	≥ 5	
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4	
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3	
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 3-4	
WATERFASTNESS STAINING			ISO 105-E01	≥ 2-3	
LABEL CE					<div style="border: 1px solid black; padding: 5px; text-align: center;">  23 EN 14041 DOP 1038-129833 NB 1611  LANO NV - Venetielaan 33 B-8530 HARELBEKE Floor carpets to use in buildings </div>
RECOMMENDED INSTALLATION					ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - SHORT PIN MUSHROOM TAPE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

MANUFACTURING TOLERANCE

COLOURS	AVAILABLE FROM			AVAILABLE FROM		
	KT 400	SOK	KT 500	KT 400	SOK	KT 500
	0120	CORAL	0120			
	0130	ROSE	0130			
	0140	OLD ROSE	0140			
	0180	RUM	0180			
	0240	CREAM	0240			
	0250	MAGNOLIA	0250			
	0260	CAMEL	0260			
	0290	SEPIA	0290			
	0370	GOLD	0370			
	0410	LEATHER	0410			
	0430	BAMBOO MAT	0430			
	0440	IVORY	0440			
	0450	SAND	0450			
	0460	HEMP	0460			
	0500	OLIVE	0500			
	0620	SAVANNA	0620			
	0700	NAVY	0700			
	0800	EBONY	0800			
	0810	CHARCOAL	0810			
	0820	SLATE	0820			
	0860	GRANITE	0860			
	0870	SILVER	0870			
	0871	GREYSTONE	0871			
	0890	SNOW	0890			



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE