

RHINOFLOOR SUPER DELUXE

DATASHEET

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	ISO 10874	23 Heavy
Commercial classification	ISO 10874	31 Moderate
Binder content	ISO 11638	Type I
Technical characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	4.0 mm
Wear layer thickness	ISO 24340	0.25 mm
Total weight	ISO 23997	2050 g/m ²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0007-0080-DOP-2024-10
Reaction to fire	EN 13501-1	Cfl-s1
Slip resistance	EN 13893	Class DS ($\mu \geq 0.30$)
Slip resistance (ramp test)	EN 16165 national Annex NB.2	R10
Electrostatic propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	ISO 10456	0.05 m ² · K/W
Technical performance	Norm	Tarkett Value
Residual indentation	ISO 24343-1	≤ 0.35 mm
Impact sound reduction – ΔL_w	EN ISO 717-2	21 dB
Colour fastness to light	ISO 105-B02	≥ 6
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (subfloor maximum temperature 27°C)
Dimensional stability	ISO 23999	≤ 0.15 %
Curl resistance	ISO 23999	≤ 8 mm
Sustainability performance	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts & post-use* – contact Tarkett for more information
Recycled content		34 %
TVOC emissions after 28 days	EN 16516	Gold (≤ 100 µg/m ³)
French VOC rating		A+
Phthalate content		Phthalate-free
Formaldehyde emission	EN 717-1	E1
Dimensions and designs		Tarkett Value
Roll		Roll 2 × 24 m Roll 3 × 24 m Roll 4 × 24 m
Number of designs available		13
Product ID		Tarkett Value
Domestic warranty (in years)		10

* Loose-laid installed



The above information is subject to modification for the benefit of further improvement (20/03/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.